

SPIRALJACK ADJUSTABLE PEDESTALS & COMPONENTS

Vegetated roofs have different depths, necessitating a flexible pedestal system that can support differing heights. Our SpiralJack Pedestal system:

- has a **height range from 5/64" - 42 5/8"** for use with concrete, wood, porcelain, and stone pavers or tiles
- features **slope correction up to 4%**
- meets **all necessary spacing sizes**, dependant on your paver size and spacing requirements
- provides **flexibility**; all components and accessories are easily inserted or removed from the pedestal
- does not penetrate or compromise waterproofing membranes due to its **large flat base** and **rounded edges**



• Full Box



• 20 Boxes per Pallet

TECHNICAL DATA

Materials:

- Recycled Polypropylene resistant to mold, alkali, & bitumen

Base Diameter:

- 7 43/64" (195 mm)

Height Range:

- 5/64" - 42 5/8" (2 mm - 1083 mm)

Slope Correction:

- 0-4%

Spacer Tab Thicknesses:

- 1/8" (3 mm)
- 5/32" (4 mm)
- 3/16" (5 mm)

Compressive Resistance:

- 1,984 lbs. minimum

Standard Kit:

- Pedestal Base
- Pedestal Top
- **PPC-TSP** Spacer Tab
- **PPC-SHM-2** Neoprene Shims


Additional Components & Accessories:

- **PPC-EXT** Adjustable Height Extender
- **PPC-TSC** Top Slope Corrector
- **PPC-BSC** Bottom Slope Corrector
- **PPC-BCL** Bearer Holder
- **PPC-WUA-B** Basic Wind Uplift Assembly
- **PPC-WUA-C** Concealed Wind Uplift Assembly

Product # 311/312




312-PPC-TSP
Spacer
Tab




312-PPC-SHM-2
Neoprene
Shims




312-PPC-EXT
Adjustable Height
Extender



312-PPC-TSC*
Top Slope
Corrector




312-PPC-BSC*
Bottom Slope
Corrector




312-PPC-BCL*
Bearer
Holder



312-PPC-WUA-B*
Basic Wind Uplift
Assembly



312-PPC-WUA-C*
Concealed Wind Uplift
Assembly



311-
PPE-2 311-
PPE-7 311-
PPE-13 311-
PPE-16

5/64" 1/4" 1/2" 5/8"
2 mm 7 mm 13 mm 16 mm



311-
PPE-18 311-
PPE-28 311-
PPE-36 311-
PPE-52 311-
PPE-82 311-
PPE-133 311-
PPE-189 311-
PPE-260 311-
PPE-364 311-
PPE-471 311-
PPE-576 311-
PPE-682 311-
PPE-786

3/4"-1" 1"-1 1/2" 1 1/2"-2" 2"-3 1/4" 3 1/4"-5 1/4" 5 1/4"-8 7/8" 7 1/2"-11 1/2" 10 1/4"-14 3/8" 14 3/8"-20" 18 1/2"-25 5/8" 22 5/8"-31 1/4" 26 7/8"-37" 31"-42 5/8"

18-25 mm 28-40 mm 36-51 mm 52-82 mm 82-135 mm 133-225 mm 189-293 mm 260-365 mm 364-507 mm 471-651 mm 576-795 mm 682-939 mm 786-1083 mm

* Dimensions in inches are nominal. Metric dimensions are actual.
* Slope correction necessary for roof pitches greater than 1/4" per foot