

PORCELAIN PAVERS

Our Porcelain Pavers use a proprietary binding agent that fuses a concrete base to the ceramic top, ensuring the base and porcelain surface will not separate over time. Ideal for use in public or private environments, these pavers offer many advantages:

- modular tiles are **removable**, allowing the gap created underneath the floor to be **easily inspected** and can house electric cables and hydraulic pipes
- 1/8" auto-spacers on sides of pavers allow for the **proper drainage** of water
- ideal for **medium to heavy traffic**
- **easy to clean**; porcelain pavers can be cleaned with standard household cleaners or pressure washed with a low pressure washing device



LEED Credits available for:

- Sustainable Sites (SS)
- Energy & Atmosphere (EA)
- Materials & Resources (MR)



- Special order product



- Full Pallet
- Full Load



- 12/24 - 52 Pavers per Pallet (104 ft²)
- 24/24 - 26 Pavers per Pallet (104 ft²)
- 26 Pallets per Load

TECHNICAL DATA

Paver Dimensions (L x W x H):

PSB-12/24 11 13/16" x 23 5/8" x 1.6"

*Pearle & Smoke Only

PSB-24/24 23 5/8" x 23 5/8" x 1.6"

Paver Weight:

PSB-12/24 18.19 lbs. / ft²

PSB-24/24 18.22 lbs. / ft²

Compressive Strength:

- 8,347 lbs. / in²

Flexural Strength:

- 970 lbs. / in²

Water Absorption:

- 6.36%

Freeze-Thaw Durability:

- Complies with standard

Slip Resistance:

- Pass

Stain Resistance:

- Class 5

Scratch Hardness (ASTM C1895):

- 8.0

Fire Rating:

- Class A

Product #

318

STONE FINISH



CEMENT IVORY



TRAVERTINE IVORY



QUARTZ SILVER



QUARTZ GREY